

System Engineering International PowerPack 300



The PP300 is an auxiliary power pack designed to increase the powering capabilities of the PowerRack 300-U. The PP300 provides an additional 250 watts of capacity for load requirements that exceed the rated capacities of the PowerRack 300-U. Alternatively, the PP300 upgrades the PowerRack 300-U to N+1 power redundancy. The PP300 simply plugs into an existing installed PowerRack and can be either wall or rack mounted (mounting hardware for 19" racks is included; mounting brackets for 23" or 25" racks may be ordered as an option by specifying 23RM or 25RM after the model number). The PP300 has an alarm contact to monitor the loss of AC power or rectifier failure. The PP300 can also be utilized as a power spare to allow on-line maintenance of the PowerRack 300-U.



Ordering Information

Model #	Description	Dimensions (W" x D" x H")
PP300	External 250 Watt power supply for PR300-U	19 x 5.25 x 5.25

Technical Specifications

Electrical	Environmental
Input Voltage: 120 VAC +10%/-15% (240 VAC Factory Option) Output Voltage: 42-56 VDC	Temperature: -20 °C to +40 °C Humidity: 95% non-condensing
Standards	
UL 1012, CSA 234	

To Order Contact ISDN Sales at 1-800-765-4734
 Visit us on the web at www.seipower.com